



SCL Colour Guard



What does it do?

SCL Colour Guard is a solvent based smooth wall coating designed as an external decorative and protective finish, which is hard wearing and long-lasting with the added benefits of year round application and a shower proof finish within twenty minutes.

Where can it be used?

Suitable for the decoration of external substrates including concrete, brick work, asbestos, cement and renderings. Also suitably primed aluminium, iron work and surfaces previously painted with emulsions or oil paints.

Details

- Application** Can be brush, roller or spray applied.
- Colour range** See colour chart overleaf: Blossom, Cream, Magnolia, New Stone, White & Candy Pink, plus other colours available to order.

Not to be used on high density, low suction substrates such as glazed blocks, faience tiles and engineering bricks.

- Spread rate** As a general guide between 50-100m² per 25 litres (2-4m² per litre) per coat.

Dependent on the thickness applied, the nature of the substrate, temperature and application method.

- Drying time** Drying is mainly by evaporation of solvent, dependant on the thickness of the coating, it may take two or three days to be through dry.

Can be applied at any temperature above 3°C.

Care should be taken to avoid brush, roller or spraying wet surfaces. In cold weather, walls must be free from retained frost.

- Shelf life** Up to two years if stored correctly in an unopened container.

Preparation

Damp walls It is important that very damp or wet walls are not coated. Building faults that allow moisture to enter walls, e.g. broken rainwater downspouts, guttering and coping stones etc. should be repaired before coating.

Experienced applicators can assess this situation to verify suitability, however if in any doubt please contact Seamless Coatings for further advice.



Algae or fungi

Algal or Fungal deposits should first be removed by power washing the surface and then treated with **Seamless Coatings Fungicidal Wash Solution**.

Loose or friable Surfaces

The substrate to be coated should be sound, free from dirt, grease, oil, dust, chalk and friable material. However, soundly adhering render with a friable surface, should be pre-treated with **Seamless Coatings Clearshield Primer**.

Cracks

Hairline cracks can be successfully covered but substantial cracks should be filled with an approved sealant.

Bitumen surfaces

Bitumen surfaces (including Bitumastic paints) should be sealed with a proprietary P.V.A. binder.



Application

Brush, roller or spray may apply **SCL Colour Guard**. Coverage will be determined by the thickness applied, the nature of the substrate, temperature and application method.

Roller type

Depends on surface type, but a heavy pile is generally used for smooth surfaces up to a maximum of a 12" roller.

Previously painted surfaces (rough cast walls)

As a guide between 50–100m² per 25 litres (between 1-4m² per litre) per coat.

DO NOT THIN

Unpainted surfaces (rough cast walls)

As a guide between 25–50m² per 25 litres (between 1-2m² per litre) per coat.

Thin 1st coat up to 5% with white spirit to produce a smooth finish.

Cleaning

Clean all brushes and equipment with white spirit.

Colours

Available in the following colours:

New Stone	Blossom	Cream
White	Magnolia	Candy Pink

* Colours shown are approximate and for indication only

Precautions

- **Flammable** keep away from sources of ignition
- Ensure good ventilation during application
- Wear gloves, goggles and suitable protective clothing
- In case of contact with eyes rinse immediately with plenty of water and seek medical advice
- Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water
- Keep out of reach of children
- Do not use near fishponds
- Toxic to aquatic environments
- Do not empty into drains

Technical support

If you would like any information on SCL products please call: **01384 413815** or email us at: **sales@seamlesscoatings.co.uk**

Disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith, but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Seamless Coatings be liable for consequential or incidental damages.

Seamless Coatings A division of IMG Composites Ltd

Unit 18, Oak Street Industrial Estate, Cradley Heath, West Midlands B64 5JY **Office:** 01384 413815 **Fax:** 01384 413830

www.seamlesscoatings.co.uk